

\* The picture is for illustration purpose only, weapon and ammunition are not provided.

## **Key Features**

- Lightweight and compact gimbal
- Operates up to 50 caliber (12.7) machine guns
- Stabilized system Designed for dynamic or static operation
- Equipped with Electro-Optical Gimbal IO/IR
- Dimensions: 120 x 75 x 55 cm

## Equipped with a built-in C2 graphical user interface, and powered by AI analytics



- Picture in picture video
- Automatic object tracking
- Moving map software



## | System parameters

GENERAL				
Dimensions	120 x 75 x 55 cm			
Rotation Diameter	1.3 m			
Unit weight	75 kg			
Input Voltage	28 – 48 VDC			
MAIN PEDESTAL				
Pan / Tilt Range	Pan: Nx 360°; Tilt: -20° - +60°			
Speed	0.01 – 100 °/s			

## | Camera parameters

		RCWS-900-1C- CS7.62/12.7	RCWS-900-1C1T150- CS7.62/12.7	RCWS-900- 1C1T150HD- CS7.62/12.7	RCWS-900-1CU1T225- C7.62/12.7	
DAY / STARLIGHT	Image Sensor	1/1.8" Sony Starvis progressive scan CMOS				
	Focal Length	6.8mm-300mm, 42x Optical Zoom			11.3mm-1000mm, 88x Optical Zoom	
	DORI Distance (Human)	Det': 2,900m ; Obs': 1,160m ; Rec': 586m ; Ide': 293m			Det':16,000m; Obs':6,300m; Rec': 3,200m; Ide':1,600m	
	Day / Night	Electrical, ICR (Auto/Manual)				
	Network Protocol	RTSP				
	Communication Protocol	SONY VISCA, HTTPS				
THERMAL / SWIR	Image Sensor	-	Uncooled VOx microbolometer			
	Resolution	9-	Sensor- 640 x 512; 50Hz: 25fps	Sensor- 1280 x 1024; 25fps	Sensor- 640 x 512 ; 25fps	
	Focal Length	-\	30mm~150mm, 5x Optical / 4x digital Zoom	30mm~150mm, 5x Optical /8x digital Zoom	25~225mm, 9x Optical / 8x digital Zoom	
	Network Protocol	- \	RTSP, HTTPS			
	Pixel size	-	12 µm			
	Spectral Range	-	8-14 µm			

